

SODIMM DDR2 PC2-5300 667 MHz



Features

- ▶ Fully PC2-5300 Compliant (DDR2 667)
- ▶ Backward compatible with PC2-4300 (DDR2 533)
- ▶ JEDEC-Standard 200-pin Small Outline Dual Inline Memory Module (SODIMM)
- ▶ Unbuffered
- ▶ Cas Latency 5
- ▶ Power Supply: 1.8V \pm 0.2V
- ▶ 64ms, 8k refresh
- ▶ Serial Presence Detect (SPD)
- ▶ Pure Power and Ground Planes
- ▶ Gold PCB connector



Ordering Information

	DENSITY	REFERENCE	EAN
Optima	1GB	SODI101GBN/5300/2-BX	3536401460534
Optima	2GB	SODI102GBN/5300/2-BX	3536401460626
Optima	Kit 2GB (2x1GB)	K-SODI2GBN/5300/2-BX	3536401002277
Premium	1GB	S1GBN08Q667F-SB	3536401462354
Premium	2GB	S2GBN16Q667F-SB	3536401461906
Premium	Kit 2GB (2x1GB)	KS2GBN08Q667F-SB	3536401002581

All of our capacities are also available in Premium packagings for distribution and integration purposes.



Optima
packaging



Premium
packaging

Product and specifications discussed here in are for evaluation and reference purpose only and are subject to change by PNY Technologies without notice.

Not sure of your
memory needs ?

Try our online
configurator !

PNY.EU



For more information, visit : **WWW.PNY.EU**